

Automatic Double Heads Sleeve Labeling Machine with Shrink Tunnel MTTB-2450



Application:

Shrink sleeve labels are widely used for labeling the shrinkable film (PVC/PP/PET/OPS/PLA) on square bottle and round bottle

Features:

- Adopt electrical configurations from Japan, French, Germany, such as Panasonic brand include PLC, frequency changer, servo driver/motor, Schneider brand include air switch, currency protector, electromagnetic contactor and Sweden hot air blower. All these components ensure our product high stability and veracity
- Standardized center mould achieve the goal of changing different products quickly
- Synchronous separating bottle design keep bottles from swaying in delivery process
- Exclusive adjustable knife unit cut label neatly and reduce cutting flaw vastly, and also the knife can be replaced easily
- Two machines into one body structure designing, bottle body and cap can be sleeving in one time

Technical Parameter:

Production speed	<i>Max.36000BPH (label height100mm. higher label height, machine speed will be slower)</i>
Bottle diameter range	<i>Φ20mm-Φ130mm</i>
Knife plate range	<i>Φ20mm-Φ50mm;Φ50mm-Φ95mm; Φ95-Φ130mm</i>
Label height	<i>25mm-300mm</i>
Label material	<i>PVC/PP/PET/OPS/PLA</i>
Label thickness	<i>0.03mm-0.13mm</i>
Paper tube inner diameter	<i>5"-10" is available</i>
Power	<i>AC 3-PHASE 440V/380V, 6.0KW</i>
Main machine size	<i>2500mm(L)*860mm(W)*2000mm(H)</i>
Machine body & Weight	<i>Stainless Steel/Painted Steel, 1000KGS(around)</i>
Shrink tunnel	<i>Heat or steam shrink tunnel is optional</i>