

High Efficiency Automatic Labeling Machine for Bottle SED-PT



The model SED-PT Top labeling machine suit for different kind products that need labeling on top surface or on the corner, such as box, carton, bags and so on.

Equipment function characteristics

- 1) Control system: Use SIEMENS brand PLC control system, with high stable operation and extremely low failure rate.
- 2) Operation system: The man machine control 7 inch touch screen, directly visual interface easy operation, rich with help function and fault display function.
- 3) Check system: Use German LEUZE check label sensor, automatic check label station, stable and convenient don't have much higher requirement for worker.
- 4) Send label system: German Avery labeling engine control system, stable with high speed.
- 5) Alarm function: Such as label spill, label broken or other malfunction during machine working all will alarm and stop working.
- 6) Machine Material: Machine and spare parts all use material S304 stainless steel and anodized senior aluminum alloy, with high corrosion resistance and never rust.
- 7) Low voltage circuit all use the German Schneider brand.

Main technical Data:

| Model | SED-PT |
|----------------------------------|---|
| Capacity (pcs/min) | 20-200 |
| Driving Mode | Servo motor |
| Labeling accuracy | ±1mm |
| Labeling Speed(m/min) | ≤35 |
| Label Specification | adhesive sticker, transparent or opaque |
| Suit bottle size | Can customized |
| Suit label size | Height 20-160mm Length 25-300mm |
| The inner diameter or label roll | 76mm(min) |
| The outer diameter of label roll | 350mm(max) |
| Power | 550w |
| Voltage | can customized, 110V/220V/380V |
| Machine size | 1800x80x1500mm |
| Voltage | 110v/220v/380v |