

Sleeve-Type Sealer With Tray Model SSA-600, SSA-800



Sleeve-Type Sealer with Tray Model, SSA600 / SSA-800 has strong & simple mechanism for easy adjustment & operation. It can run multiple package without customization; furthermore, machine can be worked either inline or off-line automatically.

Features:

- Machine adopted constant sealing knife with stable temperature & easy replacement.
- Powder painted steel frame.
- Automatic operation of feeding, pushing & sealing to work with heat tunnel, especially it can run PE or PVC for big size carton, multiple package & package with tray for shrink pack.
- Machine can made of straight or 90 degree push feeding by user's order.
- Multiple packages with paper tray.
- Full series shrink tunnel are available for different packaging requirement.
- PLC control system can detect film running and alarm of trouble to indicate problem helping technician fix machine easy.

Specification:

SSA-600

- Power: 3Ø 220V 50/60HZ
- Machine Dimension: 2500x1400x730 (m/m)
- Sealing Bar Length: L 600 (m/m)
- Max. Package Height: H 200 (m/m)
- Heater: 0.6 (KW)
- Motor: AC 1/4HP x 1, AC 60W x 2
- Packaging Capacity: 15 (Boxes/Min)
- Air Pressure Required: 5.5 (80psi) KG/cm²

SSA-800

- Power: 3Ø 220V 50/60HZ
- Machine Dimension: 2000 x 1420 x 1600 (m/m)
- Sealing Bar Length: L 800 (m/m)
- Max. Package Height: H 300 (m/m)
- Heater: 0.8 (KW)
- Motor: AC 1/4HP x 1, AC 60W x 2
- Packaging Capacity: 10 (Boxes/Min)
- Air Pressure Required: 5.5 (80psi) KG/cm²