

Corner Side Labeling Machine



Machine Performance and Feature:

1. This machine adopts PLC control, touch screen, and has the advantages of labeling accuracy, high precision.
2. This machine has high speed working and stable performance;
3. It has the functions of no bottle without labeling, automatic correction and detection.
4. This machine can be used to connect with production line or work alone.

Machine Parameters:

| | |
|---|---|
| Applicable Label Length (Mm) | 20mm ~ 200mm |
| Applicable Label Width (Bottom Paper Width /Mm) | 20mm ~ 160mm |
| Size (Length X Width X Height/Thickness) | Length (Conveying Direction): 20mm ~ 90mm Width (Conveying Width Direction): 30mm ~ 90mm |
| | Height: 60mm ~ 200mm |
| Ramp Speed (PCS /Min) | Step: 30 ~ 160pcs/Min |
| | Servo: 40 ~ 180pcs/Min |
| Weight (Kg) | About 330kg |
| Voltage (V) | 220V |
| | Rated Power (W): 1100W (Traction Step) |
| | 1600W (Traction Servo) |
| Shape Size (Mm), (Length X Width X Height) | 3000mm X 1450mm X 1600mm |

| | |
|-----------------------------------|--|
| Apply Marking Outer Diameter (Mm) | Push 280mm |
| | Internal Diameter Of Applicable Marking Volume (Mm) |
| | Marking Accuracy (Mm) |
| Weight (Kg) | About 330kg |
| Frequency (HZ) | 50HZ |