



DXDB-J80C Vaseline Pouch Back-side Sealing Packing Machine



Characteristics:

- An adopted PLC programmable control is incorporated with an English and Chinese display screen, thus making it easy to operate and maintain as well as simple to adjust. Fully automatic.
- Photoelectric tracking system and two-way compensate function are adopted to ensure correct and accurate double-face printing and counting.
- Shell is made of full stainless steel, with high corrupt proof, easy to clear, fit to GMP request.
- Granule feeding adopts measuring cups, power feeding use screw type and liquid feeding adopted piston pump for measuring.
- Cutting can choose flat cutting, fracture line cutting or saw-tooth cutting, and can choose whether match with ribbon coding machine.

Usage:

It is suitable to packing catsup, thick paste material in the medicine, food, daily chemical and other industry, automatic packing into sachets with measurement requirement. Such as peanut oil, tomato paste, cough syrup, shampoo, cream oil, Vaseline and so on.

Technical Parameter:

Pouch length	50-120mm (adjustable)
Pouch width	20-80mm
packing speed	30-60 times/min
Filling capacity	2-50ml /bag
Cutting	Flat cutting, with tear notch
Applicable film	PET/AL/PE PET/PE NY/AL/PE NY/PE/aluminize/complex film
Electric source	380V 50Hz (do as customer's request)
Total power	1KW
G.W.	260 Kg
Package size	1100*800*1600mm(L×W×H)