

LQ-BTA-450/LQ-BTA-450A+LQ-BM-500 Automatic L Type Shrink Wrapping Machine



1. BTA-450 is an economical fully-auto operation L sealer by our company's independent research and development, which is widely used in mass production assembly line with auto-feeding, conveying, sealing, shrinking in one time. It is high working efficiency and suits for the products of different height and width;
2. The horizontal blade of sealing part adopts vertical driving, while the vertical cutter uses international advanced thermostatic side cutter; The sealing line is straight and strong and we can guarantee seal line in the middle of the product to achieve perfect sealing effect;
3. When it packs different sizes, the adjustment is very simple by rotating the hand wheel to increase the reliability;
4. The machine adopts the most advanced PLC programmable controller, with safety protection and alarm devices, while the sealing system can have a continuous sealing order without replacement; Maintenance is very simple;
5. Feeding length controls through a combination of electric eye detection and time relay to control precise film length that makes it easier to control the contraction effect;
6. Two groups of horizontal and vertical electric eyes are easy to switch for thin or small packages which can easily complete sealing packaging operations;
7. Automatic rolling waste material: Using a separate motor to control which is not too loose or too tight to crack and is easy to remove the waste;
8. Feeding table and collecting conveyor are optional.

LQ-BM-500 Shrink Tunnel:

1. It adopts roller conveyor, high temperature resistant silicone tube each drum outsourcing can free rotation.
2. Stainless steel heating tube, internal three layer heat insulation, high power cycle motor, bi-directional thermal cycling wind heat evenly, constant temperature.

3. Temperature and conveying speed can be adjusted, ensure contract products to have best packing effect.

4. Hot air circulation channel, return type heat furnace tank structure, hot air only run within the furnace chamber, prevent heat loss effectively.

Technical Parameter

Model	LQ-BTA-450	LQ-BM-500
Max. Packing Size	(L+H)≤500 (W+H)≤430 (H)≤150 mm	(L)700*(W)400*(H)200 mm
Max. Sealing Size	(L)550*(W)450mm	(L)1000*(W)450*(H)250mm
Packing Speed	30-35 packs/min	0-15 m/min.
Electric Supply&Power	220V, 50Hz, 1.3 kw	380V, 50Hz, 12 kw
Air Pressure	5.5 kg/cm ³	/
Weight	500 kg	260 kg
Overall Dimensions	1800*800*1600mm	1300*700*1400mm