



YK granulator machine is a kind of small swing granulator. It is used to make moist or dried powder substance into the needed granular particles. Chuan Chu Company mainly supplies YK60, YK90 AND YK160A oscillating granulators. They are typically used in laboratories and also extensively applied in pharmacy, chemical industry, food, pottery and plastics, etc.

Features:

- 1. The screen stencil or screen mesh of YK swing granulator is easy to assemble and disassemble. The tightness can be adjusted within a particular range.
- 2. Due to the totally-enclosed mechanical transmission system and lubricant system, our oscillating granulators can work stably.
- 3. The seven-angle roller is easy to install, dismantle and clean. The rotating speed of the roller is adjustable.
- 4. YK swing granulator is designed and manufactured conforming to the GMP requirements.
- 5. The outside surface of oscillating granulator is sealed with high-quality stainless materials, making it quite durable.

Technique Parameters of YK Swing Granulator

Model	YK60	YK90	YK160A
Roller Diameter (mm)	60	90	160
Capacity (kg/h)	20-30	50-100	200-300
Oscillation Angle	> 360°	> 360°	> 360°
Oscillation Frequency (times/minute)	46	50	55
Motor Power (kW)	0.55	0.55	42402
Weight (kg)	55	150	330
Overall Size (mm)	460 × 550 × 570	750 × 460 × 840	970 × 560 × 1240