

FPC450/590 Pillow Bag Flow Wrapper



Applications:

Pillow bag flow wrapper

Food: biscuit, cake, bread, wafer food, instant noodle, stick in bag, bag in bag

Daily use product: electrical switches, tape, soap, cups, bearing, soap, cosmetic

Pharmacy: injection non-pvc bag

Typical Packaging Application:

-individual package of pillow bag

-connect with auto-feeder for high speed production

-connect with carton packer for bag in box

-connect with case packer for big case package

Features:

1. Generous machine design for high standard
2. Two servo Motor driven for accuracy control
3. Adjustable bag former for various bag size
4. Two roller device, easy change roll film
5. High integration with PLC control and HMI
6. Photocell-Tracking detect color mark for elegant package

Technical Dates:

Model	FPC450	FPC590
Film Width (mm)	<450	<590
L: Length (mm)	L: 100-400	L: 100-400
B: Width (mm)	B: 10-150	B: 30-200
H: Height (mm)	H: 10-60	H: 10-60
Speed (Bag/min)	40-180	40-180
Dimension (mm)	5000×900×1750	5000×1040×1750
Film Material	compound Film of heat seal: OPP/PE, PT/PE, AL/PE, etc	
Weight (kg)	1000	1200
Motor Power	Host motor 1.1KW one set film motor 0.75KW	
Heating Power	450W, 2 sets	
	400W, 4 sets	
Main Power	Single phase 220V, 50HZ	
Total Power	4.5KW	

Bag Samples:

