

## *FAC-207/FAC-209 Multiple Packaging Machine*



### **Merits:**

- The shrinkable film is considerably cheaper than carton. There are no problems in applying bar code on the film. Stable packs and good stacking qualities.
- Good protection for bottles and cans against contamination - clean, sanitary and good moisture resistance. Protection for bottled products against the effects of UV radiation.
- The film can be printed for specific promotional advertising effects, and inserted coupons for sales promotion. Encourages the sale of multipacks instead of single products. Products are easily distinguished & managed. PE film can be recycled.
- It's very easy to do arrangement on production line. Simple & clean appearance is the best equipment for GMP factory.
- It's equipped with safety alarm devices including the sealing safety sensor, non-film sensor, upside-down cans sensor and film breakage sensor. There are photo eyes following up the register printed film.
- The machine body is made by painted steel or stainless steel and Aluminum alloy material.
- It's easy & fast to adjust different packing structures.
- The machine is controlled by PLC program, so the actions are smooth. It's simple to operate the control panel.

### **Special Explanations:**

- The standard working height is 750 +/- 50mm. Special working height can be made as per customer's requirement.
- The in feed conveyor (as shown A figure) can connect with the production line.
- The position of the control cabinet is optional.
- If the pack formation is 7x2, 1x3, 3x4, 2x4, 2x5 or PET bottles, the machine can be additionally designed.
- The in feed conveyor can be additionally equipped with the dispersing mechanism.
- The upper film is surface printed film, the lower one in transparent film.

## Specification

Model	Pack formation	Packing size L x W x H	Film type	Packing speed (packs/min)	Applications	Air pressure	Dimension L x WxH	Weight
FAC-207	2x2	210 x 160	Printed film	25~30 (Up to 30 packs/min)	Cans, glass or plastic bottles	5~6 kg/cm <sup>2</sup>	2400 x 1150 x 1990	600 KGS
FAC-207T	2x3	x 180	Unprinted film	25~35 (Up to 35 packs/min)				
FAC-209	2x2	300 x 200	Printed film	20~25 (Up to 25 packs/min)		5~6 kg/cm <sup>2</sup>	2400 x 1150 x 1990	750 KG
FAC-209T	2x3	x 320	Unprinted film	20~28 (Up to 28 packs/min)				

## Features:

- Register printed or unprinted shrinkable film can choose.
- The machine is the most suitable for PE printed material to make the great value of products.
- Various pack formations can meet the trend of wholesale.
- Fast packing speed can match the production line prosperously.
- To assure the quality without being damaged, to save electricity and to increase profits.
- Heat oven for contracting will send out even heat radiation. Delivery is done by rollers with durability.
- Special air flow directional construction for color/non-color film, can shrink products beautifully and smoothly.
- Variable speed tunnel conveyor, automatic thermostat controls, simple operation.
- Silicone rubber coated conveyor belt rods.