



## *GS-C Measure Cup Filling Packing Machine*



It's suitable to use in packing the high accuracy and easy fragile material, such as: puffy food, crispy rice, Potato Chips, Snacks, candy, pistachio, sugar, apple slices, dumpling, chocolate, pet food, small wares etc.

### **Main performance and functional characteristics:**

- Equip with safety protection, and comply with firm safety management request;
- Use double feeding packing fabrication, fast packing speed, high efficiency, covering a little area, saving resources;
- Precision, reliability and intelligentized level;
- Make different bag shapes and punching holes according to customers, requirements;
- The body structure is made of stainless steel, artistic and durable.
- Selected installations:
  - Linked bags or multi-bags cutting functions;
  - Pothook holes punching function (circle hole and other different abnormal holes);
  - Different back seal patterns available;
  - Gusseting device, bags with self-standing functions.

### **Usage:**

Suitable for measuring and packing anomalous lumpish and granule materials, such as candy, popped food, biscuit, roasted seeds and nuts, granulated sugar, deep-frozen food, milk powder, mild tea, amyllum, sauce and so on.

## The major performance and structural feature

- \*Imported PLC computer control system with human-machine interface; touch screen is simple and direct-viewing in operation;
- \*precise positioning with servo film transporting system; excellent complete machine performance and nice packing;
- \* minimize the loss with complete automatic warn protection function;
- \* supported with metric device, the machine will automatically complete all packaging processes from measuring, feeding, filling, bag ma
- \* The way of bag making: the machine can make pillow-type bag and standing bag according to customer's requirements.

### Technical parameter:

Model	GS-C320	GS-C420	GS-C520	GS-C620
Packing speed	5-60 bag/min	5-60 bag/min	5-60 bag/min	5-50 bag/min
Bag size	(L)50-250mm	(L)50-350mm	(L)50-350mm	(L)150-400mm
	(W)60-150mm	(W)100-200mm	(W)150-250mm	(W)150-300mm
Bag making mode	Pillow-type bag, standing bag, punch bag	Pillow-type bag, standing bag, punch bag	Pillow-type bag, standing bag, punch bag	Pillow-type bag, standing bag, punch bag
Range of measuring	150-750ml	150-1000ml	150-1500ml	300-2000ml
The maximum width of packing film	320mm	420	520	620
Thickness of film	0.04-0.08mm	0.04-0.08mm	0.04-0.08mm	0.04-0.08mm
Air consumption	200L/min	200L/min	200L/min	200L/min 0.7×105Pa
	0.7×105Pa	0.7×105Pa	0.7×105Pa	
Main power/voltage	2.2KW/220V	2.2KW/220V	2.8KW/220V	3.2KW/220V 50-60Hz
	50-60Hz	50-60Hz	50-60Hz	
Dimension	L1400×	L1400×	L1600XW	
	W970×H1600mm	W970×H1600mm	1400XH2000 mm	
The weight of switchboard	400kg	450	500	800