

High Speed Auto Packer 1 Row New LQ HS-1 Row (SERVO-TYPE)



Feature

- The machine is designed to be used in 3-side and 4-side.
- The length of products is adjusted automatically. For widths, simply replace films and the I-Mark will automatically start tracking it.
- No air can be inserted in the process for its liquid sealing.
- A single machine allows packing of multiple types of products.
- This machine can pack 1-row and 2-row of 50-gram products or lighter (optional), and 1-row (A-type: 3 - 200g) and (B-type: 50 - 350g).
- The main body of the machine is produced in the SUS-6T which makes it semi-permanent.
- The filling method adopts the SUS pump which makes it possible to add or reduce filling at any time during operation.
- A flashing light is turned on 2 minutes before the film is finished. When the films are completely consumed, the machine will stop at its designated position.

Contents

Sauce, soy sauce, gravy, seasoned paste with condiments, other relevant liquids

Packing material

AL+PE, OPP+PE, NY+PE, Other Packing Papers Available for Heat Sealing

Specification

Packing row	1 Row (production option)
Capacity	30~200 EA/min
Packing size	W : 40~125 × L : 60~200mm (option)
Filling capacity	1~250g (option feature)
	(1~100g) (50~200g) (100~350g)
	A B C
	According to the filling quantity speed controls
Power consumption	Domestic : 220/380V×60Hz - AIR 5 ~ 7 Kw/h
	Overseas : 220/380/440/50×60Hz - AIR 5 ~ 7 Kw/h