

Automatic Disc Rotary Sealing Machine – CE-801/LD



Function and Configuration:

1. Manually put the box, automatically seal, one or more (depending on the product), automatically out of the box. It can be equipped with automatic cup dropping, automatic suction film, and filling machine according to the actual situation of the product.
2. Can be connected to the production line, unmanned operation, saving main power and improving production efficiency.
3. Taiwan PLC program control, stable and reliable, the man-machine interface is a touch screen.
4. Classic digital display temperature control meter, the temperature difference is plus or minus 5 degrees, and the sealing effect is good.
5. Equipped with fault alarm and temperature alarm functions to ensure the sealing effect.
6. Taiwan photoelectric eye tracking, electrical integration.

Technical Parameter:

Model	CE-801/1LD
Brand	FULLWELL
Production speed	600-700 boxes/hour (Seal a box at a time)
	1200-1500 boxes/hour (Seal two boxes at a time)
	*Determined according to the shape of filling material and container
Sealing material	Plastic composite film or aluminium foil composite film that is consistent with the cup material and can be heated and boned, such as composite PP, composite PE, composite PET, composite PS, etc
Air pressure	4-8kg/cm ²
Adjustable temperature range	Room temperature -300 degrees
Power	500-1000w
Voltage	220v or 110v (Can be customized)
Machine size	1000 x 1000 x 1500mm (customized products, subject to actual conditions)
Machine appearance	Stainless steel + aluminium profile
Net weight	200kg