TINTITU"

Printing Band Sealer FRBM-810III



- INDUSTRIAL GRADE CONTINUOUS BAND SEALERS. FRBM-810III is a continuous band sealer that will seal a wide range of plastic bag materials such as nylon, polypropylene, laminates, tyvek/polyester and foil at a high speed.
- Our unique height adjustable stand with locking casters makes it flexible to move to a certain place.
- It adopts constant temperature control system and stepless speed adjusting transmission mechanism. Temperature and speed can be easily adjusted to acquire the right seal.
- The coder is able to print at high speed with instant dry and highly legible letters that have good adhesion property. Various colors are selectable.
- The printing wheel in the machine can be used for both R arrange and T arrange of types. For types in R arrange, the machine can print two lines in font size two (18PT) or three lines in font size five (10.5PT). Counting device is optional.

Parameters:

Model	FRBM-810III
Voltage (V/Hz)	AC 220/50 110/60
Motor Power (W)	50
Sealing Power (W)	300×2
Printing Heating Power (W)	40×2
Speed (m/min)	0-12 (0-16)
Sealing Width (mm)	10
Temperature Range (°C)	0-300
Printing Type	Solid-Ink Roller
Distance from Sealing Center to Conveyor Table (mm)	20-40
Distance from Base plate to Interior Conveyor (mm)	65-85
Conveyor Table Size (L × W) (mm)	954×153
Overall Conveyor Loading (kg)	≤3
External Dimensions (L × W × H) (mm)	950×550×825
Net Weight (kg)	35