

SL-SBD/SN450 Full Automatic Double-Twisting Packing Machine



SL-SBD/SN450 double or single twisting packing machine for candy, chocolate, biscuit, etc. Compatible with a variety of sizes, shapes and wrapping materials. Single layer and double-layer wrappers can be done by one machine. It is compatible with a single and double twist, offers the most selectivity for you, makes the best value of the match

Product Details

- Full Automatic Double-Twisting Packing Machine
- Double-twisting packing machine suitable for round or cuboid chocolate or candy bars.
- The candy is usually wrapped and sealed by twisting conjunctiva wrapping paper.
- Our equipment is compatible with single- and double-twisting packaging, which can be single- or double-layer paper packaging.
- The Double-Twisting Packing Machine's speed ranges from 200 to 350 candies per minute, depending on the size of the candy.
- The product qualification rate is high, do not waste wrapping paper.

Our Technical advantage:

1. Adopt an intelligent control system In, real-time to show the working parameter, easy to operate.
2. Application of various electrical components to ensure perfect working. The shell is used cast iron, making the shell extra strong and no vibrative. High-strength mechanical transmission system (with a complete oil bath system) offers the most accurate running and guarantees a durable, nice wrapping appearance. and the service life is extra long while the wear and tear is kept low level.
3. Online detect the feeder of material and automatic regulator of the feeder speed.
4. Paper feed according to material signal. And shut off when the paper was out.

Technical Parameters

Model	SL-SBSN450
Working Capacity:	200-350 pcs/min (According to the size)
Confection Size:	Cuboid : L:15-55 W:5-30 H:5-25 (mm)
	Cylinder: 15-32 (mm)
Total Power:	5.0KW
Power Input:	380V 50HZ 3PH (Customized)
Air Supply:	Pressure: 0.6MPa Flow: 0.6 M ³ /Min
Wrapper Material:	Foil, Wax paper, BOPP.etc.(Easy to fold)
Wrapper Width :	Max.130mm
Wrapper Roller Size :	Inner Dia:76-90mm,Outer Dia≤300mm