

SED-120P-F Multifunction Capsule Blister Packaging Machine



Feature

1. It adopts the newest type high-power transmission mechanism to arrange the chain and drive the main driving shaft. The errors and noises of other gear wheel transmission can be avoided.
2. Imported controlling system is adopted; also it can be equipped with detecting and rejection function device for number of medicines according to the user's requirement.
3. It adopts photoelectrical controlling system to make PVC, PTP, Aluminum/Aluminum material to be automatically fed and waste side to be cut automatically to guarantee the Synchronous stability of over- length distance and multi stations.
4. It adopts photoelectrical controlling system to make PVC, PTP, Aluminum/Aluminum material to be automatically fed and waste side to be cut automatically to guarantee the Synchronous stability of over- length distance and multi stations.
5. The machine is suitable for industries of foodstuff, medicine, medical instruments, hardware, electronics and etc for packing.

Product Parameters

Model	SED-120P-F
Punch frequency	10-33times/min
Production capacity	1980plates/hour
Max. Forming area & Depth	130x80(standard depth ≤ 15 mm), Max. Depth 25mm(As adjusted
Standard Stroke range	30-80mm(can be designed as per user's required)
Standard plate size	80x57mm (can be designed as per user's required)
Air pressure	0.4-0.6Mpa
Compressed air required	Air compressor ≥ 0.3 m ³ /min
Total power supply	220V 50Hz 2.4Kw
Main motor	0.75Kw
PVC hard Film	0.15-0.5*110毫米(mm)
	0.15-0.5*110 (mm)
PTP Aluminum film	0.02-0.035*110 (mm)
Dialysis Paper	50-100g*110毫米(mm)
	50-100g*110(mm)
Mould cooling	Tap water or Recycling water
Overall Dimension	1900mmx600x1100 (mm)(LxWxH)
Weight	Net 425kg Gross weight: 475kg
Noise index	<75dBA