

T1650FZ full-automatic pre-stretch wrapping



Control system:

- HMI easy to operate separate top, bottom & up-down wrap count selectors
- Photo-eye pallet height sensor
- Reinforce wrap allow more wrap on same point
- Film tension adjustment on the HMI panel
- 3-12 rpm variable turntable speed by frequency changer

Turntable:

- Reset function when wrap cycle finished
- Heavy duty chain drive
- Soft start/soft stops
- Film carriage
- Powered pre-stretch film with ratio 1: 2.5
- · Film feeding speed by separate AC drive motor
- Heavy duty double chain carriage lift, calm and safety
- Other
- Hinged mast for easy handling
- Rear& front for lift inserts

Option:

- Ramp
- Top plate
- Packing height: 2800mm
- Turntable diameter: 1800mm, 2000mm
- Turntbale capacity: 2500kg, 3000kg

Advantages:

- 1. Durable using, our wrapping machines can be used for super 10 years which is approved by most of our customers
- 2. Easy operation, we improve the machine according to 20 years experience to make it more human friendly, safe and easy operation.
- 3. Film head with special design:
 - Special design of pre-stretching film head with function of film stretching Max 300%.
 - With door for easy threading of film, also with film sensor to stop the machine if the film is broken.
 - Safety crush prevention device

Technology Data:

Max load size (mm) $1100(L) \times 1100(W) \times 2400$ (H)

Turntable diameter 1650mm
Turntable height 93mm
Turntable weight capacity 2000kg
Turntable speed 3-12rpm
Machine weight 700kg

Electrics 220v, 50HZ, 1Phase

Power 1.5KW

Machine dimensions (mm) 2625(L)×1650 (W) ×2890 (H) Packing efficiency 30-50 load/h base on load

Structure part: Tower + Turntable + Film carriage + Auto film tail cut