

Automatic Sleeve Labeling Machine with Shrink Tunnel MTSL-100



Application:

Shrink sleeve labels are widely used for Labeling the shrinkable film(PVC/PP/PET/OPS/PLA) on square bottle and round bottle

Spec and Features:

- Fast and efficient reloading system, saving time and being safety.
- Adjustable high speed electric eyes lock label precisely
- Standardized center mould achieve the goal of changing different products quickly.
- Synchronous separating bottle design keep bottles from swaying in delivery process.
- Exclusive adjustable knife unit cut label neatly and reduce cutting flaw vastly, and also the knife can be replaced easily.
- Advanced operation system coordinated with touch panel and assistant buttons are more convenient and humanized
- Adopt electrical configurations from Japan, French, Germany, such as Panasonic brand include PLC, frequency changer, servo driver/motor, Schneider brand include air switch, currency protector, electromagnetic contactor and Sweden hot air blower. All these components ensure our product high stability and veracity.

Technical Parameter:

Main machine size	1000mm(L)*860mm(W)*1800mm(H)
Machine body & Weight	Stainless Steel/Painted Steel, 500KGS(around)
Power	AC 3-PHASE 220V/380V
Main machine power	2.5KW
Production speed	Max 9000BPH-12000BPH
Bottle diameter range	Φ20mm-Φ130mm
Knife plate range	Φ20mm-Φ50mm; Φ50mm-Φ95mm; Φ95-Φ130mm
Label height	25mm-300mm
Label material	PVC/PP/PET/OPS/PLA
Label thickness	0.03mm-0.13mm
Paper tube inner diameter	5"-10" is available
Shrink tunnel	Heat or steam shrink tunnel is optional