



PE Film Packing Machine



- Specially designed for bundle packing of beer, drinks and beverage, fruit juice, bottle water, dairy, condiment and so on with or without bottom support.
- Unique film layoff mechanism and constant tension film conveyor are adopted, featuring instantaneous film cutting, automatic film connecting and wrapping and higher strength after shrinking packing.
- Equipped servo motor control system, bottle-feeding, film feeding, film cutting and film wrapping are accurate, synchronous, stable and reliable.
- The LCD touch-screen has a friendly operation interface, and it is rapid for parameter setting and convenient for human-machine communication, operation and control.
- Shrink tunnel uses unique air circulation configuration, transfer belt runs smooth, wearable and with longer service life.

Parameter:

Output	Up to 60 packages per minute
	Remard: Product and film characteristic may affect machine output
Size Range	
Package cut-off length	50-6000mm
Product width	max.215mm
Product height	max.90mm
Packaging Material Reel	

Packing material	PE film or compound film
Film thickness	25~80μm
Reel diameter	≤300mm
Core diameter	≤75mm
Packaging material width	max.450mm
Weight	max. 33KG
Connections	
Voltage	220V,50HZ
Power usage	4KW
Machine weight	960kg
Machine dimensions	L4200mm*W1000mm*H1300mm
Blade cut type	Box motion
Motor configuration	3 servo motors and 2 variable frequency motors
Optional Device	date printer, auto feeder, gas charger, etc.