



## ***SP-350B/D Bread Packaging Machine***



### **Main feature:**

1. Double inverter control, the bag length is set and cut, there is no need to adjust the air go, in one step, saving time and film.
2. Man-machine interface, convenient and quick parameter setting.
3. Fault self-diagnosis function, fault display at a glance.
4. High-sensitivity photoelectric eye color tracking, digital input sealing position, make sealing position more accurate.
5. Temperature independent PID control, better suited to a variety of packaging materials.
6. Positioning stop function, no sticking knife, no waste film.
7. The transmission system is simple, the work is more reliable, and maintenance is more convenient.
8. All controls are implemented by software, which facilitates functional adjustments and technical upgrades and never lags behind.

### **Scope of application**

It is suitable for packing various kinds of regular objects such as biscuits, mating, snow cake, egg yellow pie, chocolate, bread, instant noodles, moon cakes, medicines, daily necessities, industrial parts, cartons or trays.

**Performance parameters:**

<b>Model</b>	<b>SP-350B/SP-350D</b>
Film width	Max.350mm
Bag length	120~280mm or 65~190mm 150~330mm or 90~220mm
Bag width	50~160mm
Product height	Max.45mm Max. 60mm
Film roll diameter	Max.320mm
Packing speed	40~230 bags/min
Power Specifications	220V, 50/60HZ, 2.6KVA
Machine size	(L)4020×(W)745×(H)1450
Machine quality	900Kg