

## *Manual Shrink Wrap Machine GG-FM5540*



Manual shrink wrap machine is based on widely absorbing the advantages of similar products at home and abroad, using the company's technology, characteristics and comprehensive improvement and design. To overcome the shortcomings of similar products, the use of a new structure, highlighting the humanized design, more simple and convenient operation.

### **Manual Shrink Wrap Machine Features:**

- Shrink wrap tunnel is galvanized mesh conveyor belt, suitable for PE, POF,PVC and other kinds of thermal shrink film.
- The shrinking furnace has an air-conditioned inner circulation duct design and a powerful turbine rotor. The shrink film can be uniformly heated in all directions, and the “expansion-exhaust-shrinkage” is completed in an instant to achieve perfect packaging effect.
- Using heat insulation fiberboard and unique internal circulation system, specially made seamless stainless steel electric heat pipe heating up quickly and evenly, PID automatic temperature control, electricity consumption is only 50% of similar China shrink wrap machines.
- The roller bar conveyor with rotation function can completely avoid hot stamping on the bottom of the package.
- Durable, for special products can also choose teflon mesh belt transport.
- The air duct inside shrinkage tunnel can be adjusted according to different shapes of packaging.
- The manual shrink wrap machine can be customized according to customer requirements and product size.

<b>Model</b>	<b>GG-FM5540</b>
Voltage	220-240V / 50-60Hz
power	3.8KW
Max. packing dimension (L*W*H)	550*400*300mm
capacity	500pcs/h
Machine size (L*W*H)	1400*730*1450mm
Machine weight	128kg