

Automatic Paste Packing Machine DXDG Series



Automatic vertical filling and closing machine DXDG series uses a piston dosing system and an electronic packet length adjustment by means of PLC-controller. Dose adjustment is carried out stroke. As a heat-sealable packaging material used composite materials, such as paper / PE, Cellophane / PE, aluminum foil / PE, BOPP / PE, Nylon / PE, etc.

The stages of the packaging process: the formation of the package, a clear product dosage, filling of the product package, sealing, counting units of packaged goods.

The devices can be equipped with different options according to the wishes of the customer.

Application:

Automatic vertical filling and closing machine series DXDG used for filling and packaging liquid and pasty products in the food, chemical, medical and other industries.

Options:

	DXDG-20 II	DXDG-50 II	DXDG-100 II	DXDG-500 II	DXDG-1000 II
Voltage (V/Hz)	AC 220/50 110/60		AC 220/50 110/60		
Power (W)	1300		1700	1500	1700
Packing Capacity (ml)	5-10	10-50	20-100	50-500	100-1000
Capacity (bags/min)	50-80	40-70	30-60		25-60
Length of Bag (mm)	50-150	80-150	80-220	50-220	50-250
Width of Bag (mm)	30-90	30-110	30-150	30-150	50-220
External Dimensions (L×W×H) (mm)	790*600*1780	800*700*1900	1002*860*2000		
Net Weight (kg)	350	400	400		500