



Automatic Premade Stand Up Bag Doypack ZD6-250 /ZD8-200/ZD8-320/ZD10-200



Rotary Premade Pouch Packing Machine can be equipped with multihead weigher mechanism. This equipment is specialized in granule, such as coffee bean, grain, chips, cookies, puffed food, peanut, chile, dry fruits, frozen fruits, pasta, beans, chia seeds, gum, refined gourmet powder, granular drug, capsule, seed, chemistry condiment, granulated sugar, candy, chicken essence, melon seeds, nuts, pesticide, fertilizer, etc. So this machine can also be customized as Pasta Packing Machine and Beans Packing Machine, etc.

Features:

- 1) Automatic Rotary Packing Machine adopt precision indexing device and PLC to control each action and working station to make sure the machine operates easily and does accurately.
- 2) The speed of this machine is adjusted by frequency conversion with the range, and the actual speed depends on type of products and pouch.
- 3) Automatic checking system can check bag situation, filling and sealing situation.

The system shows

- 1.no bag feeding, no filling and no sealing.
- 2.no bag opening/opening error, no filling and no sealing
- 3.no filling, no sealing.

4) The product and pouch contact parts are adopted stainless steel and other advanced material to guarantee the hygiene of products.

Application:

This product can be used to different area with optional auxiliary devices.

1. Solid Species: candy, peanut, green bean, pistachio, crystal candy, brown sugar, cookie, cake, daily commodities, cooked food, pickles, puffed food, etc.
2. Granule Species: grain, refined gourmet powder, granular drug, capsule, seed, chemistry condiment, granulated sugar, chicken essence, melon seeds, nuts, pesticide, fertilizer, etc.

Technical Parameters:

Model	ZD6-200	ZD6-250	ZD8-200	ZD8-320	ZD10-200
Working position	six-working position	six-working position	eight-working position	eight-working position	ten-working position
Pouch material	Laminated film	Laminated film	Laminated film	Laminated film	Laminated film
Pouch pattern	stand-up&zipper	stand-up&zipper	stand-up&zipper &3side sealing&4side sealing	stand-up&zipper& 3side sealing&4side sealing	stand-up&zipper
Pouch size	W:150-260mm L:150-350mm	W:200-330mm L:150-450mm	W:60-200mm L:150-380mm	W:200-320mm L:100-400mm	W:130-250mm L:120-360mm
Speed	10-50pouches/min	10-50pouches/min	40-60pouches/min	10-30pouches/min	6-55pouches/min
Weight	1350KGS	1500KGS	1200KGS	1400KGS	1000KGS
Voltage	AC38V±10%, 3Phase50HZ	AC38V±10%, 3Phase50HZ	AC38V±10%, 3Phase50HZ	AC38V±10%, 3Phase50HZ	AC38V±10%, 3Phase50HZ
Total power	3.0KW	3.0KW	2.5KW	2.5KW	3.5KW
Compress air	air consumption 0.6m³/min	air consumption 0.6m³/min	5-8kg f/cm², air consumption 0.4m³/min	5-8kg f/cm², air consumption 0.4m³/min	5-7kg f/cm², air consumption 0.5m³/min
Bag open	Vacuum open	Vacuum open	Vacuum open	Vacuum open	Vacuum open
Alarm situation	no bag no material, no sealing ,overload alarm Low pressure alarm	no bag no material, no sealing ,overload alarm Low pressure alarm	no bag no material, no sealing ,overload alarm Low pressure alarm	no bag no material, no sealing ,overload alarm Low pressure alarm	no bag no material, no sealing ,overload alarm Low pressure alarm