

## High Speed Auto Packer 1 Row LQ HS-1 Row (SERVO-TYPE)



### Feature

- The machine is designed to be used in 3-side and 4-side.
- The length of products is adjusted automatically. For widths, simply replace films and the I-Mark will automatically start tracking it.
- No air can be inserted in the process for its liquid sealing.
- A single machine allows packing of multiple types of products.
- This machine can pack 1-row and 2-row of 50-gram products or lighter (optional), and 1-row (A-type: 3 - 200g) and (B-type: 50 - 350g).
- The main body of the machine is produced in the SUS-6T which makes it semi-permanent.
- The filling method adopts the SUS pump which makes it possible to add or reduce filling at any time during operation.
- A flashing light is turned on 2 minutes before the film is finished. When the films are completely consumed, the machine will stop at its designated position.

### Contents

Sauce, soy sauce, gravy, seasoned paste with condiments, other relevant liquids

### Packing material

AL+PE, OPP+PE, NY+PE, Other Packing Papers Available for Heat Sealing

## Specification

Packing row	1 Row (production option)
Capacity	30~200 EA/min
Packing size	W : 40~125 × L : 60~200mm (option)
Filling capacity	1~250g (option feature)
	(1~100g) (50~200g) (100~350g)
	Ga      Na      Da
	According to the filling quantity speed controls
Power consumption	Domestic : 220/380V×60Hz - AIR 5 ~ 7 Kw/h
	Overseas : 220/380/440/50×60Hz - AIR 5 ~ 7 Kw/h