



GZPT26-45 tablet press



GZPT26/32/40/45 series high speed tablet press is the latest developed equipment, which fully meets the requirements of GMP, ISO and US FDA. The machine is very beautiful, presentable, easy to operate, especially since the electrical control cabinet is independent of the machine, taking into account the safety of the operator.

Perforation type (EU) D/B/BB/BBS for customer's choice. We can offer you IQ, OQ, PQ and CE as well as machines.

Perforation type (EU) D/B/BB/BBS for customer's choice.

Machine Feature:

- No flywheel system, HIM control
- Automatic weight control function
- After setting the parameters, the system will automatically control the supply or reduction of powder in accordance with the specified parameters. Achieving low deviation.
- Automatic hydraulic function

- The user can set the upper and lower values of the hydraulics, the computer controls the stable state of the hydraulics.
- Automatic lubrication system function.
- The lubrication pump is automatically controlled by the system based on timing and lubrication parameters. The user can adapt it as needed.
- Automatic deletion system function can be deleted in one batch, when deleted once, the bad part of the signal will be blown into the deletion channel
- Automatic dust removal system function
- Automatic dust removal function.

Technical Parameters:

Model	GZPT26	GZPT32	GZPT40	GZPT45
Number of forms	26	32	40	45
Die and Die Type (EU)	D	B	BB	Forum
Maximum tablet diameter (mm)	25	16	13	11
Abnormal maximum tablet diameter (mm)	25	18	16	13
Max. prepressure (kN)	20			
Max. main pressure (kN)	100	80	80	80
Maximum filling depth (mm)	20	16	16	16
Max. output (t/h)	170000	210000	260000	280000
Idle noise, dB(A)	<75			
Main motor power (kW)	380 V 50 Hz 9.5 kW			
Machine Dimensions (mm)	830×870×1995			
Net weight of the machine (kg)	1650			