

SQY-200/300/400 Sugar Coating Pan (Lab Use)



Description:

- It is widely used in the pharmaceutical, nutritional and food industries for coating tablets or pills.
- A built-in heater is provided with the machine.
- The pipe of the blower stretches into pot for an evenly heating distribution while the coating pan is rotating.
- Adjustable coating pan and LED display.
- Adjustable blower temperature and LED display.
- Changeable coating pans (Ø200mm or Ø400mm) available
- Option adopted spray gun system for film coating processing.
- Small unit, 110V powder supply, simple set-up and easy to operate.
- All stainless steel 316 construction to meet the GMP standard.
- It's easy to operate, clean, excellent performance and simple maintenance.

Specification:

Technical Data	SQY-300	SQY-400	SQY-600
Capacity	1-3kg/cycle	2-5kg/cycle	8~15kg/cycle
Pot inclination	42°	42°	30°
Motor Power	0.37kw	0.37Kw	0.75Kw
Blower Power	60W	60W	100W
Pot Volume	1L	1L	5L
Heating Power	1.4Kw	1.4Kw	2Kw
Weight	49Kg	50Kg	150Kg

Rotational Speed	0-46r/min	0-46r/min	0-40r/min
------------------	-----------	-----------	-----------

Technical Data	SQY-800	SQY-1000	SQY-1250
Capacity	30~50kg/cycle	50-70kg/cycle	80-150kg/cycle
Pot inclination	30°	30°	30°
Motor Power	1.1Kw	1.5Kw	2.2Kw
Blower Power	200W	200W	370W
Pot Volume	8L	10L	20L
Heating Power	3Kw	4Kw	6Kw
Weight	280Kg	300Kg	500Kg
Rotational Speed	0-32r/min	0-32r/min	0-28r/min