

BS-260 Shrink Packaging Machine



Shrink packaging is the use of shrink film wrapped in products or packaging outside, and then heated, so that the packaging material shrink and tighten the product or package, fully display the appearance of goods, And the protection of goods from external shocks, with a certain degree of cushioning, especially when the packaging of glass products, to prevent the glass can be used to prevent the glass, Broken in the scattered, in addition, can reduce the product was demolished, the possibility of theft;

Shrink film shrink when a certain amount of tension, it can be a group of items to be wrapped tightly wrapped.

This product is widely used in light industry, food and beverage, candy, stationery, arts and crafts, printing products, pharmaceutical products, chemical, hardware and electrical components such as shrink packaging.

Functions

- 1. The use of electronic variable speed transmission, stable and reliable, long life, low noise.
- 2. The use of quartz far infrared tube heating, work can continue to produce infrared radiation, with a strong wind cycle, so that the heating chamber temperature becomes more uniform, while saving energy.
- 3. Transmission part of the use of high-power DC motor, can be stepless speed regulation, while the bearing rate is high.
- 4. Can work continuously for a long time, and stable and reliable operation.
- 5. The use of special mechanical structure design, shape more beautiful, luxurious, and make maintenance easier and convenient.

Parameter:

Name	Shrink machine	Model	BS-260
Working efficiency	260*180mm	Conveyor	3KG Maximum
Conveyor speed	0-10m/min(adjust)	Power	3KW(adjust)
Net Weight	35KG	Voltage	220V 50HZ
Material	PVC		