

## *KENO-P450 Automatic Pillow Packing Machinery*



### **Main characteristic**

1. Double transducer control, flexible bag length cutting, operator needn't to adjust the unloading working, saving time and saving films.
2. human-machine operation, convenient and quick parameter setting.
3. Self-diagnosis failure function, clear failure display.
4. High sensitivity optical electric color mark tracking AND digital input cut position which makes the sealing and cutting more accurate.
5. Separate PID control to temperature, suitable for various packing materials.
6. Stopping the machine in selected position, no sticking to the knife and no waste packing film.
7. Simple driving system, reliable working, convenient maintenance.
8. All the controls are achieved by software, convenient for function adjusting and upgrading.

### **Application:**

Suitable for packaging various kinds of regular objects like biscuits, pies, chocolates, bread, instant noodles, moon-cakes, drugs, daily appliances, industrial parts, paper boxes, plates, etc.

### **Performance parameter**

Type	KENO-P450
Film width	Max.450mm
Bag length	130-450mm
Bag width	50~180mm
Product height	Max. 70mm
Film roll diameter	Max. 320mm
Packaging rate	30-180 bag/min
Power	220V,50/60HZ,2.6KVA
Machine size	(L)4020×(W)820×(H)1450
Machine weight	900Kg