

LSA-908A(CE) Fully Auto L-Type Sealer



Fully Auto L-sealer, LSA-908A adopted constant heat sealing cutter; POF is environmental friendly. It is only recommended to run with LSA-708A.

Machine working size is easy to adjust & operate. The individual pin wheels design can help shrink wrap well. There are many options of working features to be available such as Kissing Conveyor, Changeable Sealing Height, Hi-speed Sealing...etc.

Features:

- Adopted HMI control system to have easy size change & operation.
- The sealing line can be moved to mid of package to save the film width. Comparing to Auto L-type Sealer, it can be smaller at least 1" film size, which help save film cost.
- Adopted stepping motor to have stable sealing length of bag making.
- Sealing safety sensor prevent the product from damaging by cutting & protect sealing knife without injury.
- The TD & MD sealing knives are separated to have strong sealing line.
- The minimized wastage trim save cost.
- It has higher packaging speed with easy size change.
- The MD sealing can be working any length without limitation.
- Simple mechanism for easy cleaning & maintenance.

Specification:

- Power: 3Ø 220V 50/60HZ
- Machine Dimension: 2780 x 2090 x 1900 (m/m)
- Sealing Bar Length: 950 x 850
- Max. Package Height: 280 (m/m)
- Heater: 2.0 (KW)
- Motor: AC60 x 1, AC40 x 1, AC90 x 3, AC15 x 1
- Packaging Capacity: 10 (Boxes/Min) Box: 180 x 110 x 42 (m/m)
- Air Pressure Required: 5.5 (80psi) KG/cm²