



DK-450WSE/DK-600WSE Reciprocating Servo Pillow Packing Machine



Dustial Machinery® reciprocating servo pillow packing machine is controlled by double frequency converters, the bag length can be set and cut immediately, no need to adjust the idle, one step is in place, saving time and film. Man-machine interface, convenient and quick parameter setting. Fault self-diagnosis function, fault display is clear at a glance. High-sensitivity photoelectric eye color mark tracking, digital input of sealing and cutting position, making the sealing and cutting position more accurate. Temperature independent PID control, better suitable for various packaging materials. The reciprocating end-sealing mechanism makes the sealing more firm, and the die-sealing cutter has no loss. End-sealing gusseting device, the bag shape is more beautiful, and the product grade is improved. Positioning stop function, no sticking to the knife, no waste of film. The transmission system is simple, the work is more reliable, and the maintenance is more convenient. All controls are implemented by software, which is convenient for function adjustment and technology upgrade, and never lags behind. The advantages of Dustial Machinery manufacturer's packaging machine are remarkable

Parameters

| Type | DK-450WSE | DK-600WSE |
|---------------------|------------------------------|------------------------|
| Film width | Max 430mm | Max 580mm |
| Bag length | 120-6000mm | 120-6000mm |
| Bag width | 50-160mm | 50-200mm |
| Product height | 5-80mm | 5-100mm |
| Film roll diameter | Max 300mm | |
| Packaging speed | 20-80bag/min | |
| Packaging materials | OPP,OPP/CPP,KOP/CPP,ALU-FILM | |
| Power | 220V,50/60Hz,4.45KW | 220V,50/60Hz,4.45KW |
| Machine size | (L)3960×(W)830×(H)1780 | (L)3960×(W)930×(H)1780 |
| Machine weight | 930Kg | 1010Kg |