

Online Bottle Visual Inspection Machine



Inspection table is used to inspect the abnormalities in filling

Inspection table is equipment consisting of a three-track conveyor with a hood with lighting arrangement and visual inspection background of alternate black & white color. Inspection table have stainless steel structure with moving S.S. slat chain. Structure made out of S. S. square pipe & supported on adjustable bolts.

Salient Featuers

- A/c frequency variable drive.
- Direct gear drive.
- Length can be made as per customer requirement.
- PVC black & white board as per GMP norms.
- UHMW self lubrication guide below chain.
- SS elegantly matt finishing.
- Adjustable height of conveyor belt, to align with other machine of the line
- Self-alignment bearing for easy maintenance.
- Rigid vibration free construction for trouble free performance

Technical Specification

- Direction of Movement** Left to Right
- Output * Up to 100 Containers/minute
- Number of Operator Four (2x2, Two Side Seated)
- Power Characteristics** 0.5 HP / 220 Volts / 50 Hz.
- Height of Conveyor ** 860 mm to 910 mm
- Machine Dimensions** 1880 mm (L) x 700 mm (W) x 1525 mm (H)
- Case Dimensions** 2150 mm (L) x 950 mm (W) x 1750 mm (H)
- Net Weight 200 Kgs.
- Gross Weight 425 Kgs. Approx