

BGK SERIES HIGH-EFFICIENCY FILM COATER WITH PERFORATED DRUM



BGK SERIES OF HIGH-EFFICIENCY COATER IS MAINLY USED IN PHARMACEUTICAL AND FOODSTUFF INDUSTRIES. IT IS A HIGH-EFFICIENCY, ENERGY SAVING, SAFE, CLEAN AND MECHATRONICS EQUIPMENT FOR COATING TABLETS, PILLS AND CANDIES WITH ORGANIC FILM, WATER SOLUBLE FILM, SLOW AND CONTROLLED RELEASE FILM AND SUGAR FILM ETC. IT MEETS GMP REQUIREMENTS.

FEATURES

- 1. EASY AND FAST CHARGING AND DISCHARGING
- 2. BOTH FILM AND SUGAR COATING
- 3. PID PRECISION CONTROL
- 4. WIP SYSTEMS

ADVANTAGES

- 1. EASY AND FAST CHARGING AND DISCHARGING
- 2. BOTH FILM AND SUGAR COATING
- 3. PID PRECISION CONTROL
- 4. WIP SYSTEMS

MAIN TECHNICAL PARAMETER

Model	(Bxlxh)mm Main structure dimensions			Batch Size	Pan speed	Main machine	Air fan power	Exhaust fan	Main machine
	В	<u>L</u>	Н	(kg/ batch)	(r/min)	Power (kW)	(kW)	Power(kW)	weight (kg)
BGK5	1300	930	1685	5	5~30	0.55	0.55	1.1	1000
BGK10	1000	900	1855	10	5~30	1.1	0.75	2.2	350
BGK15	1000	930	1650	15	2~30	1.1	0.75	2.2	500
BGK25	1055	950	1645	25	2-25	1.1	0.75	2.2	350
BGK50	1260	1040	1960	50	2~25	1.5	1.1	3	520
BGK75	1260	1040	1725	75	2~25	1.5	1.1	4	520
BGK100	1570	1260	2080	100	2~18	2.2	1.5	5.5	700
BGK150	1570	1260	2080	150	2~18	2.2	1.5	5.5	700
BGK250	2000	1545	2600	250	2-14	3	3	7.5	1100
BGK350	2000	1545	2600	350	2~14	4	4	11	1100
BGK500	2100	1900	2700	500	2~14	5.5	5.5	15	1800
BGK650	2100	2150	2800	650	2~12	5.5	5.5	15	1500
BGK800	2180	2400	2450	800	2~8	5.5	5.5	18.5	2000
BGK1000	2280	2650	2550	1000	2~8	7.5	7.5	22	2300