

Label-Aire® Inline series 6200



The NEW Label-Aire® Inline 6200 labeling system offers you a wealth of options and configurations to make labeling easier and faster.

The Inline 6200's sheer flexibility allows you to build a labeling system to fit seamlessly in your production line. The Inline 6200 also delivers on Label-Aire's long-standing promise of advanced features, toughness, speed, and accuracy meaning lower operating costs and increased productivity for your business.

The NEW advanced yet rugged Inline 6200 labeling system is a stainless steel cabinet based PLC-controlled labeling system designed for heavy duty front/back-, side panel-, or wrap labeling applications. Among its standard features are a rotating control panel, a 12 foot (3,658 mm) delrin chain conveyor with stainless steel side plates, and a segmented top trap hold down to keep your products in place. Other standard features include Automatic Speed Following (ASF) for product surface profiling, Variable Frequency Drive (VFD), and dual applicator mounts with in/out traverse, up/down, with tilt adjustments for maximum versatility. Standard speeds up to 2,000 inches (50.8 m) per minute with VFD make the 6200 the ideal choice for demanding applications requiring speed and precision. The 6200's long list of options include a choice of Label-Aire New Generation 3100/3000 Series applicators (wipe-on, air-blow, or tamp-blow), wrap belt, single or dual feedscrews, stainless steel side plates, stainless steel frame, stainless steel cabinet, airfill capability, and powered or nonpowered impressors.

Put this high-speed labeling technology to work for you all day, every day. The Inline 6200 is built to meticulous quality standards and designed to work in the most hostile environments.

NOT AVAILABLE FOR THE EUROPEAN MARKET

Features

- **Main Drive:**
Line Speed Variable Frequency Drive (VFD) up to 2,000" (50.8 m) per minute
- **Conveyor:** Stainless Steel Side Plates
Width 6.0" (152.4 mm)
Length 12' (3,657.6 mm) center line-to-center line
Height 36" (914.4 mm) ± 2" (50.8 mm)
- **Applicator:** Label-Aire 3100 Series Primary Applicators
- **Operator Interface:** Dual Keypad for Applicators, Push Button Start/Stop for Conveyor
Control PLC
- **Top Trap Hold Down:** Spring Segmented Blocks, Linatex Belt
Vertical Adjustment 16.0" (406.4 mm)
Belt Width 1.25" (31.75 mm)
Drive Direct
Airfill Optional
- **Feedscrew:** Single or Dual
Length Options 30" (762 mm)
Drive Direct **Soft Start** Yes
- **Metering Wheel:** Single
Drive DC Motor
- **Wrap Belt:** 7.0" (177.8 mm) Wide x 12.0" (304.8 mm) Long
Secondary Impressors (Opt.):
Powered Available
Non-Powered Available