

Powder Automatic Packing Machine PB-6R



Feature

- It is easy to use this machine which had been minimized in noises and dusts.
- The machine has been designed in a way to replace parts easily.
- Weight can be adjusted in front of the machine and the gauge is designed in a clockwise fashion for enhanced convenience.
- The entire supply unit rotates 180 degrees to make it convenient to maintain the machine, replace parts and clean nozzles.
- This machine uses STS in a unit where the product is closed for preventing corrosion and for semi-permanent durability.
- Product packaging is available from 2-row to 8-row on demand. (optional feature)
- A flashing light is turned on 2 minutes before the film is finished. When the films are completely consumed, the machine will stop at its designated position.
- The film board can be adjusted to left and right and the phototube can be calibrated to front and back.
- The adjusting handle is installed in the front unit of a machine to operate it.

Contents

Condiments, sugar, powdered tea, granules, medical supplies, powdered milk, supplements for diet, chemical substances, other relevant products

Packing material

AL+PE, OPP+PE, NY+PE, Other Packing Papers Available for Heat Sealing

Specification

Packing row	2~8 Row (production option)
Capacity	30~60 EA/min (on 1 row)
Packing size	W : 40~125 × L : 60~195mm (option feature)
Filling capacity	1~40g (option feature)
Electric Power	220/380V, 3P, 50/60Hz
Compressed Air	5~7kgf/cm ² , 80ℓ/min