



Automatic Bag Forming Electronic Weighing Filling Packaging Machine CC-1203



Automatic Filling Packing Machine - CC-1203 suitable for filling weighing and packaging various granular products, such as crude sugar, red beans, rice, green beans and feeding stuffs etc.

Features:

- The Automatic Filling Packing Machine - CC-1203 automatic bag forming electronic weighing filling packaging machine is suitable for all types of granular products.
- The machine is designed with an air operated sealing mechanism, ensuring smooth appearance of product without pin-hole problem. No material exists at sealing position that assures superior tightness of sealing.
- Printing points photoelectric sensor is easy to adjust to eliminate waste of packaging film.
- Simply inputs packaging length in case of no printing points photoelectric sensor.
- Minimum sealing temperature variation. Employ PID calculation to maintain temperature tolerance within $\pm 2^{\circ}\text{C}$.
- Product types and weights can be memorized for added convenience of management.
- The transmission system of the packaging machine is driven by a servo motor (Mitsubishi from Japan) for high accuracy.
- The controller provides a self-diagnostic function. In case any machine trouble occurs, such as no packaging film, no color type, photoelectric sensor error, excessive or under sealing temperature or air pressure failure etc, the machine will display problem points and trouble-shooting instructions.
- Easy to set filling weight.
- Filling weight accuracy is controlled within $\pm 1\%$.

- The weighing unit features automatic reset.
- Graduation of load cell is 1g.
- Double vibration metering design.
- The machine is available to be connected with initial material system.
- The machine is available to equip with a corner insert vertical bag device.

Specification:

Model	CC-1203
Machine Size	L: 125 / W: 165 / H: 320 cm
Machine Weight	700 kgs
Range of Packaging Film Size (Product Sizes)	L: 15 - 35 cm, W: 12 - 24 cm
Packaging Speed	25 - 30 bags/min (Vary with filling weight)
Packaging Method	3-side back sealing, Gusset
Power Required	220V, 3Ø, 7.5HP, 50/60Hz
Range of Filling and Metering	300 - 2000 g