



Automatic Shrink Sleeve Labeling Machine SL-100/200/300/400/500



As a professional China drinking water bottles labeling machine automatic shrink sleeve labeling machine expert, we provide labeling machine for glass bottles automatic labeling machine.

The PVC shrink sleeve labeling machine is suitable for round bottles, flat, square bottles, curved bottles, cups and other products in food and beverage, medical, daily chemical and other light industries.

Characteristics:

- ☆ the whole machine adopts stainless steel and high-quality aluminum, well-structured, compact and easy to adjust.
- ☆ without anchor bolts can be easily mobile, flexible space with the production.
- ☆ shrink film label rack, with adjustable brake, and paper tube according to label 5"~ 10" to facilitate adjustment.
- ☆ unique set of standard methods, the use of compression-type sets of tender, in a convenient and reasonable.
- ☆ Automatic feed motors, at the same time leveling materials shrink film tension adjustment.
- ☆ Volume label detection system ensure that the minimum error.
- ☆ Unique design of the knife is special in the framework, can change blocks ATC freely, ATC quickly and easily.
- ☆ Center column clamping system, change quickly and without any tools.
- ☆ Label positioning device, according to the demand for container shape, position adjustment can be synchronized movements.
- ☆ Hours bottle-screw, positioning belt, chain adjustment using synchronous manner, and speed adjustment is simple, quick.
- ☆ Adopt Japanese servo motor and high-sensitivity photoelectric, standard length is precision
- ☆ Stainless steel electrical control box, control the use of Japan's Mitsubishi PLC.

☆ adopt advanced automatic control technology of the man-machine interface, the key electrical components are adopted internationally renowned products

Parameters:

Model	SL-100	SL-200	SL-300	SL-400	SL-500
Voltage	AC220V, 50/60HZ, 1.5-2KW (Host machine) AC380V,50/60 HZ, 18KW (Shrinking machine)	AC220V, 50/60HZ, 1.5 KW (Host machine) AC380V,50/60 HZ, 18KW (Shrinking machine)	AC220V, 50/60HZ, 2.5 KW (Host machine) AC380V,50/60 HZ, 24KW (Shrinking machine)	AC220V, 50/60HZ, 3 KW (Host machine) AC380V,50/60 HZ, 36KW (Shrinking machine)	AC220V, 50/60HZ, 3 KW (Host machine) AC380V,50/60 HZ, 36KW (Shrinking machine)
Production speed	6000 BPH	9000-12000 BPH	15000-18000 BPH	22000-24000 BPH	28000-30000 BPH
Diameter of bottle body	φ 28mm- φ 125mm	φ 28mm- φ 125mm	φ 28mm- φ 125mm	φ 28mm- φ 125mm	φ 28mm- φ 125mm
Length of label	30mm-250mm	30mm-250mm	30mm-250mm	30mm-250mm	30mm-250mm
Thickness of label	0.035mm-0.13mm	0.03mm-0.13mm	0.03mm-0.13mm	0.03mm-0.13mm	0.03mm-0.13mm
Material of label	PVC, PET, OPS	PVC, PET, OPS	PVC, PET, OPS	PVC, PET, OPS	PVC, PET, OPS
Size (label sleeving host machine)	L2000mm*W850mm*H2000mm	L780mm*W1200mm*H2000mm	L2100mm*W1100mm*H2000mm	L2100mm*W850mm*H2000mm	L2500mm*W1200mm*H2000mm
Size (Bulk of steam shrinking label)	L1800mm*W500mm*H1500mm	L1800mm*W500mm*H1500mm	L1800mm*W500mm*H1500mm	L1800mm*W500mm*H1500mm	L1800mm*W500mm*H1500mm
Steam shrinking tunnel (quantity of steam)	20Kg/H	30Kg/H	30Kg/H	50Kg/H	50Kg/H