



ROY-515B *Automatic sentinel round bottle labeling machine*



General Introduction

Dedicated to the circumferential surface of red wine bottle label, can be attached to a single standard and double standard, are back double standard spacing can be flexibly adjusted; possess conical bottle labeling function; optional peripheral location detection device can achieve the specified position in the circumferential surface labeling.

Application

- ◆ applicable Tags: adhesive label / sticker film.
- ◆ Application: Diameter 40mm ~ 90mm round bottle between.
- ◆ Industry: Widely used in wine, medicine, food, toys, cosmetics, and other industries.
- ◆ Application examples: Bordeaux bottle labeling, Tatu bottle labeling, labeling Remy, cylindrical bottle of red double standard labeling and so on.

Working process

* Core works: put the product to the conveyor belt, into the sub-bottle agencies, sub-agencies will bottle products separately, the sensor detects the product passes the signal returned to the labeling control system, the control system in place to control the corresponding motor Submit tab and be affixed to the product labeling position, while overlying standard, a label attached action is completed.

* Procedure: put the product conveyor belt (which can be accessed line) -> Product delivery -> Products minutes away -> Product Testing -> Product Positioning -> Labeling and covered Landmarks -> collect the labeling products.

Technical Parameters

Operating direction	One side/two sides
Label height	20mm~160mm
Label length	10-300mm
Diameter of bottle body	25-1500mm(conveyor belt can be customized)
Label roll inner diameter	76mm
Label roll outer diameter	<360mm
Speed	12-38meters/min
Capacity	20-60bottles/min
Machine dimensions (mm) (L xW xH)	1950mm x1200mm x1530mm
Power (W)	570W