

FPC450-3(5) Biscuit in Lines Flow Wrapper



Applications:

Pillow bag type

Food: biscuit, biscuit in lines tray-less

Typical Packaging Application:

- individual package of pillow bag
- connect with auto-feeder for high speed production
- connect with carton packer for bag in box
- connect with case packer for big case package

Features:

1. Generous machine design for high standard
2. Two servo Motor driven for accuracy control
3. Adjustable bag former for various bag size
4. Two roller device, easy change roll film
5. High integration with PLC control and HMI
6. Photocell-Tracking detect color mark for elegant package

Technical Dates:

Model	FPC450-3	FPC450-5
Film Width (mm)	<450	<450
L: Length (mm)	L:120-450	L:120-450
B: Width (mm)	B:10-150	B:10-150
H: Height (mm)	H:30-75	H:30-75
Packing Speed (Bag/min)	40-180	40-180
Dimension (mm)	5000×900×1750	5000×1040×1750
Film Material	compound Film of heat seal: OPP/PE, PT/PE, AL/PE, etc	
Weight (kg)	1000	1200
Motor Power	3 Servo Motor	5 Servo Motor
Heating Power	450W, 2 sets	
	400W, 4 sets	
Main Power	Single phase 220V, 50HZ	
Total Power	7Kw	9Kw

Bag Samples:

