

## *Shrink Sleeve Applicator HLS (E) Series*



### **Product Range:**

- High Speed Shrink Sleeve Applicator
- Super Speed Shrink Sleeve Applicator
- Standard Shrink Sleeve Applicator
- Auto Cap Banding Applicator
- Economical Shrink Sleeve Applicator
- Steam Shrink Tunnel
- Electric Shrink Tunnel

### **Features:**

- Stainless steel constructed machine body ensures superior rigidity and stability, with light weight design and pleasing appearance.
- Equipped with CE level compact gear reducer, ensuring superior quality and performance.
- Machine can be manufactured completely according to CE standard for utmost quality and safety.
- Using selected high-level drive and control system for the best compatibility and convenient maintenance.
- Advanced HMI from superior brand, combining built-in buttons with light, featuring user-friendly operation.
- Newly designed synchronizing clamping divide with motor ensures convenient adjustment and high valve.
- All optical fiber sensors set on machine are from worldwide famous brand to ensure the best accuracy.
- Multi-functional features make it possible to utilize machine with diverse devices or equipment to fulfill various production need.
- High quality with competitive price bring 100% customer satisfaction.
- Equipped with intelligent memory settlement when sleeving multiple bottle types at different speed, providing user-friendly and convenient changeover.

**Specification:**

	<b>Model</b>	<b>HLS-2350 (E)</b>	<b>HLS-2400 (E)</b>	<b>HLS-2300 (E)</b>	<b>HLS-2450 (E)</b>
<b>Machine</b>	Dimension (L W H)	1080 x 780 x 2040 mm			
	Weight	550 kg			
	Electric Power	AC - 3 Phase 220 V / 2.5 kW			
	Speed	300 BPM	350 BPM	400 BPM	450 BPM
<b>Container</b>	Diameter	Ø 10 - 125 mm			
	Height	Max 350 mm			
	Material	Glass, Metal, Plastic			
	Shape	Round, Oval, Square, Rectangular			
<b>Shrink Sleeve</b>	Material	PVC, PET, OPS, PLA			
	Thickness	0.035 - 0.08 mm			
	Inner Diameter of Sleeve Roll	5" ~ 10"			