

Automatic Shrink Sleeve Labeling Machine ES-250



Suitable for various kinds of bottle type of fruit juice, tea beverage, dairy products, pure water, condiment, beer, sports drinks such as food and beverage

- a. can set of round bottles, square bottles, elliptical bottle, bottle and body.
- b. suitable for food, beverage, cleaning products, pharmaceuticals, bottle etc all kinds of plastic bottle, glass bottle, PVC, PET, PS, tin and other containers.

Feature & Advantages:

1. The standard position precision is high, and shrinkage can highlight the perfect shape of bottle.
2. High and stable mechanical structure of the whole machine adopts stainless steel protection box cover and aluminum alloy rigid frame, solid doesn't rust.
3. High quality positioning accuracy: all mechanical transmission design, using force set timescale, and various membrane materials 0.03mm-0.13mm film thickness, membrane material applies 5-10 range inner diameter can be adjusted.
4. Low maintenance cost: the spare parts of the machine are easy to change, low cost burden.
5. Reliable after-sale service: this machine various spare parts warehouse all have spare, can offer, and experienced engineers provides technical support.
6. Exclusive design: reciprocating cutting knives, adopt high technical, rigid body movements smooth, the tool life extend one times.
7. The structure of the machine is simple and easy, can ensure low failure rate, maintenance and simple.
8. Simple type center word column positioning, specifications, the operator is convenient to use easy replacement of manipulating plain, easiness, completely avoid the user's problems.

Specifications:

| Model | ES-250 |
|------------------------------------|----------------------------|
| Power | 3.0KW |
| Voltage | AC 3 ψ 380V/220V |
| Yield capacity | 250 bottle/min |
| Dimension | 2100(L)*850mm(W)*2000mm(H) |
| Application of bottle diameter | ψ 28~ ψ 125(mm) |
| Application of label size | 30mm-250mm |
| Application of label thickness | 0.03mm-0.13mm |
| Application of paper tube diameter | 5"-10"(free adjustment) |