

JY-450/590SP Full Automatic Shrink Packaging Machine



Main performance & characteristics

1. Suitable for singly or arbitrary assembled packaging.
2. Cutting-resistance safety on-off device is set for preventing the damage of packed goods.
3. If add the waste material recovery device, it can make the packaging mostly beautiful.
4. Adjusted separately for the speed, temperature and length of the packaging, it makes the operation convenient and accuracy.
5. With the control of motor braking, the reaction of the equipment is sensitive.
6. With Chain scraper conveyor, no movement or overturn happened while sending the package.
7. Date coder and ink-jet printer are optional. No need manual work.

Using range

Suitable for heat shrink packaging of bowl or cupped instant noodles, cupped milk, bottled milk, cupped tea, noodles, tableware disinfection, soap, cosmetic and mosquito, etc.

Technical parameter

Model	JY-450SP/99	JY-450SP/120	JY-450SP/150
Packing speed (bag/minute)	50-180bag/min	50-150bag/min	50-150bag/min
Packing size (mm)	L60-400	L80-400	L100-400
Length x Width x Height	W< 150mm	W<150mm	W<150mm
	H<40mm	H<60mm	H<75mm
Maximum width of film (mm)	<450mm	<450mm	<450mm
Packing material	POF/PVCfilm	POF/PVCfilm	POF/PVCfilm
Power	Packaging machine:220V,50/60Hz,3-5Kw		
	Shrink tunnel:380V,50Hz, 15Kw		
Overall size (mm)	5000*1050*	5000*1050*	5000*1050*
	1600mm	1600mm	1600mm
Weight	1000kg	1000kg	1000kg

Model	JY-590SP/99	JY-590SP/120	JY-590SP/150
Packing speed (bag/minute)	50-150bag/min	50-150bag/min	50-150bag/min
Packing size (mm)	L70-400	L100-450	L100-400
Length x Width x Height	W<200mm	W<200mm	W<200mm
	H<60mm	H<90mm	H<100mm
Maximum width of film (mm)	<590mm	<590mm	<590mm
Packing material	POF/PVCfilm	POF/PVCfilm	POF/PVCfilm
Power	Packaging machine:220V,50/60Hz,3-5Kw		
	Shrink tunnel:380V,50Hz, 15Kw		
Overall size (mm)	5000*1050*	5000*1050*	5000*1050*
	1600mm	1600mm	1600mm
Weight	1000kg	1200kg	1200kg