

Liquid Automatic Packing Machine LQ-6R (SERVO 6-axis TYPE) Z-PRINTER



Feature

- The length of products is adjusted automatically by the Servo Motor.
- Product weight can be controlled by Touch with Digital.
- It is available without I-Mark.
- C.I.P can be done with supply unit only.
- Each unit has been installed with the safety cover and the alarming device.
- Each part has been standardized and simplified to reduce time taken for replacements. Better yet, the machine rarely generates replacement parts.
- This is the first-time ever achievement in Korea for producing a packaging machine based on the Servo 6-axis.
- The length of products can be adjusted from 70 to 200. The position calibration for the first sealing, the secondary sealing and for the cutter is done automatically.
- A flashing light is turned on 2 minutes before the film is finished. When the films are completely consumed, the machine will stop at its designated position.

Contents

Ginseng extracts, red ginseng extracts, other relevant liquid

Packing material

AL+PE, OPP+PE, NY+PE, Other relevant packing papers with 3 sides sealed available for thermal sealing

Specification

Packing row	2~8 Row (production option)
Capacity	20~40 EA/min (on 1 row)
Date Printer	Jet Printer & Others Date Printer Option
Packing size	W : 50~125 × L : 60~150mm (option feature)
	(Digital Control)
Filling capacity	4~120g (option feature)
Electric Power	220/380V, 3P, 50/60Hz
Compressed Air	5~7kgf/cm ² , 200ℓ/min