

USA-005R Auto Side Sealing Machine



Auto Side Sealing Machine, standard model USA-005R can adjust its packaging height basing on product to have strong seal & nice look. Sealing safety sensor prevents the product from damaging by cutting & protect sealing knife without injury.

POF is recommended to work with. USA-005R can reduce the film wastage & seal multiple length without any limitation.

Features:

- Adopted HMI control system to have easy size change & operation.
- The sealing line can be moved to mid of package to save the film width. Comparing to Auto L-type Sealer, it can be smaller at least 1" film size, which help save film cost.
- Adopted stepping motor to have stable sealing length of bag making.
- Sealing safety sensor prevents the product from damaging by cutting & protect sealing knife without injury.
- The TD & MD sealing knives are separated to have strong sealing line.
- The minimized wastage trim save cost.
- It has higher packaging speed with easy size change.
- The MD sealing can be working any length without limitation.
- Simple mechanism for easy cleaning & maintenance.
- Adopted continuous MD sealing design without length limitation.
- Sealing Size: No limitation length of MD seal x TD 550mm seal (L x W)

Specification

- Power: 1Ø 220V 50/60HZ
- Machine Dimension: 2120x970x1570 (m/m)
- Seal Size: ∞ x 500 (m/m)
- Max. Package Height: H 5 - 120 (m/m)
- Heater: 1 (KW)
- Motor: 4NM x 2, 40W x 1, 15W x 1
- Packaging Capacity: 40 (Boxes/Min) Box: 180 x 110 x 42 (m/m)
- Air Pressure Required: 5.5 (80psi) KG/cm²