Wilpac厨得堡®

WP-DS series Liquid Multilanes Packing Machine



Feature

- © Speed: Normally is 25-40, our machine can reach 45-50.
- © Change film: quick release and positioning function is the same as stick bag multilanes packing machine.
- © Film pulling: fast release and clamp the film and pull down always.
- © Vertical sealing: The two sets of sealing jaws can be independently controlled, the pressure is adjustable and with the spring buffer function.
- © Horizontal sealing: with buffer function, servo motor driven as option.
- © Forming: Easy film balance and front and rear film length adjustment.
- © Slitting into several lanes: adjustment and replacement is convenient.
- Multiple positioning ensures that the film will not deviate in the overall film process.

Technical Parameters

Item NO.	WP-DJ210	WP-DJ300	WP-DJ450	
Packing Lines	(The specific lanes number is determined according to the bag wide and model)			
Film Thickness	PE film, laminated film, aluminum film, DuPont paper / thickness 0.05-0.1mm / no elastic or slight elastic			
Film Width	210	300	450	
Film Roll Diameter	350			
Each Line Packing Speed	25-55/min/lane(specifically related to packaging materials)			

	<u></u>		
Bag Size Range	60 ≤ L ≤ 180		
	17 ≤ W ≤ 60		
Voltage	5KW/380V	6KW/380V	7.5KW/380V
	/50(60)HZ	/50(60)HZ	/50(60)HZ
Gas Pressure	0.4~0.8MPa	0.4~0.8MPa	0.4~0.8MPa
Gas Consumption	0.4m³ / Min	0.5m ³ / Min	0.6m³ / Min
Machine Size(mm)	1150x1900x1750	1350x1900x1750	1450x1900x1750
Machine Weight	300KG	500KG	600KG

Item NO.	WP-DJ600	WP-DJ750	WP-DJ850
Packing Lines	(The specific lanes number is determined according to the bag wide and model)		
Film Thickness	PE film, laminated film, aluminum film, DuPont paper / thickness 0.05-0.1mm / no elastic or slight elastic		
Film Width	600	750	800
Film Roll Diameter	350		
Each Line Packing Speed	25-55/min/lane(specifically related to packaging materials)		
Bag Size Range	60 ≤ L ≤ 180		
	17 ≤ W ≤ 60		
Voltage	10.5KW/380V	11KW/380V	13KW/380V
	/50(60)HZ	/50(60)HZ	/50(60)HZ
Gas Pressure	0.4~0.8MPa	0.4~0.8MPa	0.4~0.8MPa
Gas Consumption	0.9m³ / Min	1m³ / Min	1m³ / Min
Machine Size(mm)	1600x1900x1850	1750x1900x1850	1850x1900x1850
Machine Weight	700KG	800KG	1300KG