



JS-26 Automatic Computerized Weighing & Packaging Machine (Pneumatic Sealing+Weighing Scale)



Machine Features:

- PLC Control + Touch Panel for ease operation.
- Touch Panel for easy usage to set up: Filling weight, cutting mode(eye mark or length cutting), bag length, speed, counter, sealing temperature, memory record...etc.
- Auto eye mark tracing in a short time.
- Pneumatic sealing enable to set up sealing & cutting time according request.
- Pneumatic sealing construction with SMC cylinder drive for stable sealing performance.
- Sealing and cutting operations are air cylinder activated for fast, highly efficient operations.
- Pneumatic sealing type for nice sealing packaging performance.
- Auto warning display for quick trouble shooting display.
- Multiple memory programs for record different packaging data.
- Enable to adjust filling weight directly through the panel.
- 2 stages vibration loading with large & micro-feeding for smooth & accurate filling.
- Film tension control for stable film filling & pulling.
- Individual control for film pulling, sealing and cutting.
- All component in direct contact with product are made with stainless steel or food sanitary standard.
- PID function Temp. controller for each sealing part with stable sealing performance.
- Machine can be made 1, 2 or 4 scales according to request.
- Bag width is adjustable by changing bag former guide.
- Attached speed adjustable 1M product output conveyor.

- Product input conveyor is optional device, include auto refill function to work with packaging machine.

Optional Device:

Date coder, hopper level indicator, nitrogen air connector, product input conveyor...etc., and other required device upon request.

Applicable Products:

Various powder & granule products, such as:sugar, salt, macaroni, chips, popcorn, cracker, candy, tea, beans, peanuts, pet food, screws, washer...etc., or other related products.

Applicable Film:

Double layer heat sealable laminated film, such as: PET+LLDPE, PET+MPET+CPP, PET+PE+AL+LLDPE, Nylon+LLDPE...etc.

Technical Parameters:

	JS-26 Pneumatic Sealing+Weighing Scale
Sealing Style	Pillow type packaging(one option)
Power	220V, 50 or 60 Hz, single phase(upon request)
Film Width	240-480mm
Bag Length	150-300mm
Filling Weight	30-100g/100-1000g/1000-2000g (varies with product density)
Packaging Speed (1 scale)	About 8-10 bags/min
Packaging Speed (2 scales)	About 10-15 bags/min
Packaging Speed (4 scales)	About 20-25 bags/min
Machine Dimension	240 x 155 x 235cm(L x W x H)
Net Weight	880kg