CHS-6702A Random Automatic Four Edge Carton Sealer | Top & Bottom Drive

Features

- Carton dragging by Top & Bottom belts with independent motors
- Automatic adjustment of carton width and height. Continuously produce random cartons.
- Have both of regular mode (random sizes) and memory mode (uniform size)
- Carton sealing: seal the upper and lower 4 edges for strengthen
- Suitable for:
  1) Users with export demand. (Improve box support)
  2) Production line is processed by robot arm. (Reinforced box)
- PLC controlled to alter the program easily
- Infeed push-carton conveyor, the carton will be pushed off 90 degrees into the edge sealer where it completes the "H" seal top and bottom.
- Stainless roller table for carton movement
- The tape head is developed and produce by CHA PACK, the length of tape that can be placed up to 900m. (260mm diameter)
- Dual telescoping mast with cushion. Adjust the unevenness of the carton.
- Machine with mobile casters and feed, easy to move
- 7" HMI can be available as an option. To provides convenient for technician to operate and flexible adjustment of machine's parameters. To reduce the time for error elimination and accelerate the maintenance efficiency
- Bespoke designs of carton edge sealer for lower height of carton from H110mm
- Carton edge sealer is designed to meet the needs of random in-line carton closure applications

- Machine can be available with other equipment's, e.g:
    - Labeling mc.
    - Weighing mc.
    - Inkjet Printers
- Parts are manufactured with mold.- Stable quality, Short lead time
- Machines are designed and produced by ourselves. Rugged design, low maintenance rate
- 90% self-production rate, 100% Made in Taiwan.

Specification

Model	CHS-6702A
Function	Top & Bottom belt driven
Power Supply	3 phase, 220V/380V/415V
Tape Width	2" or 3"
2" & 3" Tape Sealing size	L300-650mm, W250-600mm, H225-600mm
Tape overlap	L60±5 (mm) standard
Working table height	570-770mm
Conveyor Speed	20 M/min
Capacity	4~5 cases/mins. (Random sizes)
	10~12 cases/mins. (Uniform size)
	(Data is for carton length=300mm)
	Depending on box size and operator efficiency.
Machine dimension	L2100 x W1460 x H1500mm
Air compressor	6kg/cm²