

# Multi lane Granule Back Sealing Packing Machine GH280BK / GH560BK



## Feature:

1. Famous brand PLC control, system, large touch screen, convenient to operate;
2. Advanced design, high precision and fast speed;
3. No film alarm, saving materials and no waste film;
4. Photocell tracking system for precise bag length and position of film

## Parameter:

Model	GH280BK	GH560BK
Lanes number	4-6 lane	4-10 lanes
Capacity	35 bags/min/lane basic on produce and film	35 bags/min/lane basic on produce and film
Measuring method	1~ 50ml	1~ 50ml
Measuring Accuracy	±2%	±2%
Measure Model	1.Volumetric Cup Filling ; 2.Multi heads linear weigher ; 3.Vibration bowl counting feeder	
Bag size	L:50-180MM	L:50-180MM
	W:17-40MM	W:17-85MM
Sealing type	Back sealing/stick bag	Back sealing/stick bag
Film width	Max.280mm	Max.560mm
Film thickness	Laminated film thickness:0.07--0.10mm	
Cutting type	1.Flat Cutting; 2.Zigzag cutting; 3.Continuous cutting; 4.Round cutting; 5.Customized special shape cutting	
Control system	PLC+Servo+Touch screen	PLC+Servo+Touch screen
Air consumption	0.8 MPA 0.6M3/MIN	0.8 MPA 0.6M3/MIN
Power Supply	3.5KW, 1N+PE/50HZ/AC220V	5KW, 1N+PE/50HZ/AC220V
Dimension	L1385*W918*H2005mm	L1685*W1300*H2005mm
Weight	350KG	450KG