

## *HG High Speed Shrink Sleeve Applicator (HLS Series)*



### **INFORMATION**

1. Stainless steel constructed machine body ensures superior rigidity and stability, with light weight design and pleasing appearance.
2. Equipped with CE level compact gear reducer, ensuring superior quality and performance.
3. Machine can be manufactured completely according to CE standard for utmost quality and safety.
4. Using selected high-level drive and control system for the best compatibility and convenient maintenance.
5. Advanced HMI from superior brand, combining built-in buttons with light, featuring user-friendly operation.
6. Newly designed synchronizing clamping device with motor ensures convenient adjustment and high value.
7. All optical fiber sensors set on machine are from worldwide famous brand to ensure the best accuracy.
8. Multi-functional features make it possible to utilize machine with diverse devices or equipment to fulfill various production need.
9. High quality with competitive price brings 100% customer satisfaction.
10. Equipped with intelligent memory settlement when sleeving multiple bottle types at different speed, providing user-friendly and convenient changeover.



# SPECIFICATION

	機型 Model	HLS-2300(E)	HLS-2350(E)	HLS-2400(E)	HLS-2450(E)
MACHINE 主機	長×寬×高(mm) Dimension(L x W x H)	1080x780x2040			
	重量 weight	550kg			
	電源 Electric Power	AC-3 Phase 220V / 2.5KW			
	速度 Speed	300 BPM	350 BPM	400 BPM	450 BPM
CONTAINER 容器	直徑 Diameter	φ10-125mm			
	高度 Height	Max. 350mm			
	材質 Material	玻璃、金屬、塑膠 Glass, Metal, Plastic			
	形狀 Shape	圓、橢圓、方形、長方形 Round, Oval, Square, Rectangular			
SHRINK SLEEVE 收縮 膜材	材質 Material	PVC, PET, OPS, PLA			
	厚度 Thickness	0.035-0.08mm			
	膜料紙管內徑 roll Inner diameter of sleeve	5"~10"			