

## *Packing Machine YY- 520/720*



The whole production of assembly line packaging, used in food, medicine, cosmetic, hardware, lighting, furniture and other industries (bag, bottle) products filling (filling), sealing machine, code. Mainly include: liquid (paste) filling machine, pillow packaging machine, horizontal packaging machine, vertical packaging machine, powder particle packaging machine, bag feeding automatic packaging machine, frozen products automatic packaging machine and so on.

### **Features:**

1. The use of gas control and circuit control independent separation, low noise, stable performance.
2. Packaging machine clean health, environmental protection use.
3. Save material, save bag, save cost.
4. All parts in contact with the product are made of stainless steel or rust-proof materials.
5. Good visibility of the side open protective baffle, safe operation.
6. The bag shape is good, more beautiful.
7. Achieve high precision positioning, accurate size.
8. The packing capacity can be adjusted at any time during the operation of the machine to reduce material loss and improve work efficiency
9. The use of double belt servo pull die and double servo control, less resistance.
10. Easy to use, with automatic bag making, measuring, blanking, sealing, cutting, counting, printing batch number and other functions.
11. Suitable for ordinary pillow bag and inclined bag.
12. Photoelectric cell positioning control system, accurate positioning photo eye mark.

**Parameters:**

| Type                   | YY-720                            | YY- 520                           |
|------------------------|-----------------------------------|-----------------------------------|
| Bag length             | 100-480mm (L)                     | 80- 400mm (L)                     |
| Bag width              | 180-350mm (W)                     | 60- 250mm (W)                     |
| Max width of roll film | 720mm                             | 520mm                             |
| Packing speed          | 10-60bags/ min                    | 10-600bags/min                    |
| Measuring range        | 6000ml (Max)                      | 3000ml(Max)                       |
| Air consumption        | 0.65Mpa                           | 0.65Mpa                           |
| Gas consumption        | 0.4m <sup>3</sup> / min           | 0.4m <sup>3</sup> / min           |
| Power voltage          | 220VAC/50HZ                       | 220VAC/50HZ                       |
| Power                  | 5KW                               | 4KW                               |
| Dimension              | (L)1500mm*(W)1270mm*<br>(H)1700mm | (L)1500mm*(W)1170mm*(H)<br>1500mm |
| Net weight             | 900Kg                             | 800Kg                             |