



Computerized Scale Type VFFS Packaging Machine TOP-M200-CS



Features

- Apply to various dry and solid / granule product
- Mitsubishi PLC control, easy setting / control / adjustment
- Flexible setting in weighing amount
- High accuracy in weighing
- 15 programs setting memory
- Easy-tear zig-zag cutting on sealing
- Firm multilineal sealing

Applications

- Dry and solid / granule food as snack, rice cracker, nut, popcorn, biscuit, candy, dried fruit, spaghetti, bean, pet food,.....etc.
- Bulleted breech, plastic part, gravel, spangle, bead, spar, seed,....etc.

Functions

- Productivity increasing
- Flexible package to conform different weight and requirement
- Product protection to decrease the environmental influences as microorganisms and humidity,.....etc

Dimension	TOP-M200-CS	TOP-M250-CS	TOP-M300-CS
Dimension	(L) 3500mm	(L) 3600mm	(L) 3700mm
	(W) 1250mm	(W) 1470mm	(W) 1520mm
	(H) 2020mm	(H) 2020mm	(H) 2020mm
Bag Size	(W) 50-200mm	(W) 100-250mm	(W) 150-300mm
	(L) 50-300mm	(L) 100-300mm	(L) 150-300mm
		L type : max. length up to 580mm	
Film Width	130-430mm	230-530mm	330-630mm
Film Material	NY+PE, PE, PP, OPP+CPP, Galvanization Aluminum Foil		
Capacity	PE Film : 10-20 bags/min.		
	Laminated Film : 10-45 bags/min.		
	(subject to product property, weight & filling speed)		
Power	3Ø、220V/380V、50/60Hz、3.7kw		
Air Pressure	5HP Air compressor 、5kg/cm2		