

# HESLY

## *Shrink Tunnel Type HS-8040SL/10040SL*



Beautiful machine, Stable quality, Safety, energy saving, patented products, domestic initiative, application to the POF/PVC/PP film thermal shrink packaging effect is perfect.

### **Features:**

1. Appearance and knot design in accordance with national standards, the fuselage uses fingerprint resistant sheet production after spray treatment.
2. Control panel using programming system, 12V DC input, button switch, digital display.
3. Transmission using 24v DC Motor speed control using variable frequency technology 0-9 file adjustment.
4. The conveyer belt can be used wire mesh belt, chain roller, Teflon mesh belt three.
5. Heating using 600W 220V far infrared quartz heating tube.
6. Temperature control using high precision intelligent temperature control system up and down temperature independent regulation.
7. Hot air circulation using 220V 60W 2200 to the long axis motor with wind wheel.
8. The bracket can be disassembled, and the height of the bracket can be adjusted.

**Specification:**

<b>Model:</b>	<b>HS-8040SL</b>	<b>HS-10040SL</b>
Voltage	380v 50-60HZ	380v 50-60HZ
Power	25KW	45KW
Shrink tunnel size:	1800*800*400MM	1800x1000x400mm
Product size:	700x300mm	850x300mm
Speed:	0-15m/min	0-15m/min
Conveyor material	Roller chain	Roller chain
Max weight	50kg	50kg
Machine size:	2500x1100x1650mm	2500x1300x1650mm
Machine weight	500kg	600kg
Application:	PE.POF.PVC.PP	PE.POF.PVC.PP